Digi Package Coater 25"/30"

UV/Aqueous Varnish Coater for package printing with specially developed varnish, both high quality coating and superior glueability come true!

25" version: B2 Portrait 30" version: B2 Landscape







Fuji film JetPress 750S

Digi Package Coater 25"/30" is designed for package printing and ensures high-grade UV/Aqueous Varnish Coating technology.

Digi Package Coater 25"/30" is suitable from B2/A2 digital presses and offset presses. Two separated coating stations provide fast conversion of varnish to deal with small volume printing of high variety products by short leadtime. Higher leveling coating can be realized and designed automated cleaning system helps for daily operation. By using of specially developed UV varnish which is acceptable of EVA hotmelt glue or cold/hot foil for folding carton finishing.

Specification

Coating Technology:	Sheet Fed Flood Coating for UV / Aqueous Varnish	Paper Thickness:	104 - 750gsm	Power Supply:	200V~415V, 50/60Hz Three Phase
	IR Heater and UV Cure System	*Paper thickness may not be applicable subject to the media material.		Power Consumption:	16 KW
	Simplex Coating	Coating Thickness:	6~14 Microns	Dimensions:	L 5.76m x W 1.07m x H 1.37m
	2 Station Coating Systems as option	Coating Speed:	(25") Max. 2,800 sheets / hour (B2 Portrait)	Weight:	Approx. 1740kg
Coating Paper Size:	Max. 585mm x 750mm		(30") Max. 4,800 sheets / hour (B2 Landscape)	Option: Commercial Printing Version 80 - 600gsm in paper thickness	
	(Fuji film Jet Press 750S: 585mm x 750mm)	*Speed is variable depending on the paper (type, thickness), environment (temperature, humidity), and/or coating type (varnish coating or primer coating)		* Paper thickness may not be applicable subject to the media material	
Coating Width:	(25") Max. 636mm, (30") Max. 762mm	Feeder stacking height:	850mm		
		Stacker stacking height:	850mm		

^{*}The specification may be changed without notice.

