



Business Partner



With Simplex Corona

# BN MultiCoat SX30AS/Corona

With Corona Treatment

## BN MultiCoat SX30AS

Without Corona Treatment

Spot UV/Aqueous Varnish Coater with chamber anilox roll and flexo plate for HP Indigo Digital Press 35K / 15K



HP Indigo 35K



HP Indigo 15K

BN MultiCoat SX30AS/Corona is designed to ensure high grade and high quality spot UV/Aqueous Varnish Coating with Flexo Plate

BN MultiCoat SX30AS/Corona is spot varnish coater for B2 size media. The flexo plate roller system with chamber anilox roll achieves coating ability as it matches other coating solution than UV Varnish and Aqueous Varnish. For spot coating, this unit provides smooth surface finishing. The operator can use user-friendly touch screen controller to operate fully automatic from warm-ups, coating, job setting and cleaning. The configured auto sheet feeder and auto stacker support to provide high productivity and convenience at your operations.

### Specification

Coating Technology :	Sheet Fed Spot Coating by Flexo Plate System	Paper Thickness :	70 - 450gsm (uncoated paper)	Power Supply :	200V - 415V, 50/60Hz Three Phase
	Flexo plate & Chamber Anilox System		90 - 450gsm (coated paper)	Power Consumption :	16 KW
	Simplex Coating		* Paper thickness may not be applicable subject to the media material	Dimensions :	L 6.12m x W 1.70m x H 1.37m
Coating Thickness :	Adjustable by anilox roll	Coating Speed :	Max. 50 meter / min.	Weight :	Approx. 2440kg
Coating Paper Size (Max):	585mm x 750mm		*Speed is variable depending on the paper (type, thickness), environment (temperature, humidity), and/or coating type (varnish coating or primer coating)		
	(HP Indigo 35K / 15K : 530mm x 750mm)	Feeder stacking height :	900mm		
Coating Width (Max) :	762mm	Stacker stacking height :	500mm		

\*The specification may be changed without notice.

220901 V1



BN Technology Corporation, 4-15-7 Nishi-Shinjuku, Shinjuku-ku, Tokyo 160-0023, Japan TEL: +81-3-5365-2551 URL: <http://www.bn-technology.co.jp>