

BN MultiCoat SX30P/Corona is Coater which is three in one system for Primer Coating before printing and UV/Aqueous Varnish Coating after printing.

BN MultiCoat SX30P/Corona is suitable for B2/A2 digital presses and offset presses. Two separated coating stations provide fast conversion of varnish to deal with small volume printing of high variety products by short leadtime. Higher leveling coating can be realized and designed automated cleaning system helps for daily operation. BN MultiCoat SX30P working with HP Indigo 15K/12000 is the most effective system for primer coating and UV, aqueous coating after printing.



Specification

Coating Technology:	Sheet Fed Flood Coating	Paper Thickness:	90 - 450gsm	Power Supply:	200V~415V, 50/60Hz Three Phase
	IR Heater & UV Cure System	*Paper thickness may not be a	pplicable subject to the media material.	Power Consumption:	16 KW
	Simplex Coating, 2 Station Coating Systems	Coating Thickness:	6~14 Microns	Dimensions:	L 6.00m x W 1.23m x H 1.40m
Corona Treatment Unit:	Adjustable Corona Power	Coating Speed:	Max. 50 meter / min.	Weight:	Approx. 1840kg
Coating Paper Size:	585mm x 750mm	*Speed is variable depending on the paper (type, thickness) and environment (temperature, humidity).		Option:	In-Line Solution with HP Indigo 15K
	(HP Indigo 15K/12000: 530mm x 750mm)	Feeder stacking height:	900mm		
Coating Width (Max):	762mm	Stacker stacking height:	500mm		

*The specification may be changed without notice.

230724 V2

BN Technology Corporation, 4-15-7 Nishi-Shinjuku, Shinjuku-ku, Tokyo 160-0023, Japan TEL: +81-3-5365-2551 URL: http://www.bn-technology.co.jp