

# Digi Spot Package Coater 24"/30"

Spot UV/Water-based Varnish Coater  
with chamber anilox roll and flexo plate  
for HP Indigo Digital Press 12000/30000

24" version: B2 Portrait  
30" version: B2 Landscape



HP Indigo 12000



HP Indigo 30000



Digi Spot Package Coater 24/30 is designed for package printing and ensures high-grade spot UV/Water-based Varnish Coating with Flexo Plate

Digi Spot Package Coater 24/30 is spot varnish coater compatible with digitally printed folding cartons in sizes B2. The flexo plate roller system with chamber anilox roll achieves coating ability as it matches other coating solution than UV Varnish and Water-based Varnish. For spot coating, this unit provides smooth surface finishing. The operator can use user-friendly touch screen controller to operate fully automatic from warm-ups, coating, job setting and cleaning. The configured auto sheet feeder and auto stacker support to provide high productivity and convenience at your operations.

## Specification

|                           |  |                          |   |                       |   |
|---------------------------|--|--------------------------|---|-----------------------|---|
| Coating Technology:       | Sheet Fed Spot Coating by Flexo Plate System | Paper Thickness:         | 104 - 750gsm  | Power Supply:         | 200V~415V, 50/60Hz Three Phase  |
|                           | Flexo plate & Chamber Anilox System          |                          | * Paper thickness may not be applicable subject to the media material   | Power Consumption:    | 16 KW   |
|                           | Simplex Coating                              | Coating Speed :          | (24") Max. 2,800 sheets / hour (B2 Portrait)  | Dimensions:           | L 6.12m x W 1.70m x H 1.37m   |
| Coating Thickness:        | Adjustable by anilox roll                    |                          | (30") Max. 4,800 sheets / hour (B2 Landscape)   | Weight: Coater unit + |   |
| Coating Paper Size (Max): | (24") 545mm x 788mm, (30") 750mm x 585mm     |                          | *Speed is variable depending on the paper (type, thickness), environment (temperature, humidity), and/or coating type (varnish coating or primer coating) | Stacker/Feeder unit   | Approx. 2440kg  |
|                           | (HP Indigo 12000/30000 : 530mm x 750mm)      | Feeder stacking height:  | 850mm   | Option :              | Commercial Printing Version 80 - 600gsm in paper thickness            |
| Coating Width (Max):      | (24") 610mm, (30") 762mm                     | Stacker stacking height: | 850mm   |                       | * Paper thickness may not be applicable subject to the media material |

\*The specification may be changed without notice.