



Digi Spot Package Coater 25

Spot UV/Water-based Varnish Coater with chamber anilox roll and flexo plate for KOMORI Impremia IS29, B2 digital printing press and A1 offset printing press



KOMORI Impremia IS29



KOMORI offset presses

Digi Spot Package Coater 25 is designed for package printing and ensures high-grade spot UV/Water-based Varnish Coating with Flexo Plate

Digi Spot Package Coater 25 is spot varnish coater compatible with digitally and offset printed folding cartons in sizes B2 and A1. The flexo plate roller system with chamber anilox roll achieves coating ability as it matches other coating solution than UV Varnish and Water-based Varnish. For spot coating, this unit provides smooth surface finishing. The operator can use user-friendly touch screen controller to operate fully automatic from warm-ups, coating, job setting and cleaning. The configured auto sheet feeder and auto stacker support to provide high productivity and convenience at your operations.

Specification

Coating Technology:	Sheet Fed Spot Coating by Flexo Plate System	Paper Thickness:	157 - 600gsm	Power Supply:	200V~415V, 50/60Hz Three Phase
	Flexo plate & Chamber Anilox System	Coating Speed:	Max. 30 meter/min. - UV Coating	Power Consumption:	16 KW
	Simplex Coating		Max. 30 meter/min. - Water-based Varnish Coating	Dimensions:	L 5.80m x W 1.10m x H 1.40m
Coating Thickness:	Changeable by changing anilox roll		*Speed is variable depending on the paper thickness, media and/or varnish	Weight: Coater unit +	
Coating Paper Size:	Max. 636mm x 939mm	Feeder stacking height:	850mm	Stacker/Feeder unit	Approx. 2440kg
	(KOMORI Impremia IS29 : 585mm x 750mm)	Stacker stacking height:	850mm		
Coating Width:	Max. 636mm				

*The specification may be changed without notice.

170430 V2

