



**Digi CASE-IN**



Case-in machine to finish hard cover book binding of short run jobs. Book block and hard cover are joined simply with precise registration. Easy operation and book size adjustment can handle flexible cover size and book format.



**Digi PRESSDA**

Digi PressDA is two-stage press machine with safety design such as door interlocking and effective finisher with press board divided into upper and lower stage with high performance.



**Digi JOINT-FORMER**



Digi Joint-Former makes fine groove on a joint between cover and book spine. Simple operation with pressure and heater temperature adjustment is best benefit for short-run finishing of book.

Product speed:	Approx. 150 books/hour	Press capability:	800 kgf/cm <sup>2</sup>	Production speed:	Approx. 100 books/hour
Book size:	136x136 ~ 400x400mm	Pressing board size:	Max. 820mm x 560mm	Book size:	136x136 ~ 400x400mm
Book thickness:	8 ~ 60mm	Pressing material thickness:	Max. 240mm	Book thickness:	8mm ~ 60mm
Glue/Air consumption:	Cold(water glue)/0.60Mpa	Operation:	Automatic operation with door interlocking and timer / Manual operation	Press position alignment:	~40mm
Glue coating method:	Roll coating	Air consumption:	0.60 Mpa	Timer setting range:	~5 minutes
Glue supply/Glue tank:	Pump circulation method/External tank	Power supply:	200V 0.5KW 3A	Temperature setting range:	Ordinary temp. ~120°C
Power supply:	200V 1KW 5A	Dimension:	1000(W)x650(D)x1434(H) mm	Air consumption:	0.60 Mpa
Dimension:	700(W)x865(D)x1410(H) mm	Weight:	200 kg	Weight/Power supply:	110kg/200V 2KW 10A
Weight:	280 kg	※ External air compressor is needed.		Dimension:	500(W)x530(D)x1039(H) mm
※ External air compressor is needed.		※ External air compressor is needed.		※ External air compressor is needed.	